



Stud Welding Machines

CAPACITOR DISCHARGE STUD WELDING RANGE



SM-I



SM-II



SM-III



SM-IV

MODEL	STUDMASTER-I	STUDMASTER-II	STUDMASTER-III	STUDMASTER-IV
Stud Range	M3-M8 (M.S, SS, Brass, Aluminium)	M3-M8 (M.S, SS, GI Brass, Aluminium)	M3-M10 (M.S, SS, GI Brass, Aluminium)	M3-M12 (M.S, SS, GI Brass, Aluminium)
Input Supply	230VAC,50Hz,Single Phase			
Welding Method	Tip Ignition			
Charging Capacity	75,000 µf	99,000 µf	132,000 µf	165,000 µf
Charging Voltage	20-180 VDC			
Digital Display	For Charging Voltage			
Input KVA	0.75	0.85	1	1.25
Gun Type	Standard Contact Gun with 4 mtr Highly Flexible Cable			
Ground Cable	Highly Flexible 4 mtr with Earth Clamp			
Dimensions (L x W x H)	22"X11.5"X14"	22"X11.5"X14"	26"X11.5"X14"	26"X11.5"X14"
Weight with accessories (Approx)	29.5Kg	31.5Kg	37.5Kg	39.5Kg